



Thermostat, RT14

017-509966

Product name: Thermostat, Type: RT14, Reset function: Auto, Contact function: SPDT, Temperature range [°C] [Min]: -5, Sensor type: Remote bulb, Temperature range [°C] [Max]: 30

**Contact: 0982 67 24 67 -
online@congnhieplanh.com**

Product details

Gross weight	0.98 kg
Net weight	0.86 kg
EAN	5702428519250

Ambient temperature range [°C] [Max]	70 °C
Ambient temperature range [°C] [Min]	-50 °C
Ambient temperature range [°F] [Max]	158 °F
Ambient temperature range [°F] [Min]	-58 °F
Approval	CCC CE EAC GL LVD NKK

	PZH RMRS RoHS RoHS China TYSK CMIM LLC CDC EURO-TYSK
Cap. tube length fraction [in]	78 3/4 in
Capillary tube length [mm]	2000 mm
Charge type	Adsorption
Contact function	SPDT
Contact rating	AC15=3 A, 400 V AC1=10 A, 400 V DC13=12 W, 220 V AC3=4 A, 400 V LR=28 A, 400 V
Diff. @ Max. range setting[°C] [Max]	10 °C
Diff. @ Max. range setting[°C] [Min]	2 °C
Diff. @ Min. range setting[°C] [Max]	8 °C
Diff. @ Min. range setting[°C] [Min]	2 °C
Differential type	Adjustable
Electrical conn. Male/Female	Female
Electrical connection	Screwed cable entry
Electrical connection size	2xPg 13.5
Electrical connection standard	DIN 40430
Electrical spec. standard	EN 60947-4/-5
EN 60947 electrical properties	Pollution degree: 3 Rated impulse voltage: 4 kV Short circuit prot, fuse: 10A
EN 60947 wiring properties	Flex, ferrules: 0.2-1.5 mm ²

	Flex, no ferrules: 0.2-2.5 mm ² Solid/stranded: 0.2-2.5 mm ²
Enclosure rating IP	IP66
Equipment	
Max. sensor temperature [°C]	150 °C
Max. sensor temperature [°F]	302 °F
Packing format	Multi pack
Product accessories	Switches accessories
Product description	Thermostat
Product family name	RT thermostat
Product group	Switches and thermostats
Product name	Thermostat
Quantity per packing format	15 pc
Reset function	Auto
Sensor pocket length min. [in]	4 13/32 in
Sensor pocket length min. [mm]	112 mm
Sensor size (Ø x L) [in]	3/8 x 4 1/4 in
Sensor size (Ø x L) [mm]	9.5 x 110 mm
Sensor type	Remote bulb
Serviceable	Contact systems
Temperature range [°C] [Max]	30 °C
Temperature range [°C] [Min]	-5 °C
Temperature range [°F] [Max]	86 °F
Temperature range [°F] [Min]	23 °F
Type	RT14

