



Pressure transmitter, MBS 3000 060G1125

Product name: Pressure transmitter, Type: MBS 3000, Pressure range [psi]: 0.00 - 145.04, Pressure range [bar]: 0.00 - 10.00, Output signal [mA]: 4 - 20, Electrical connection size: Pg 9, Electrical connection: DIN-plug

Contact: 0982 67 24 67 -
online@congnhieplanh.com

Product details

Gross weight	0.17 kg
Net weight	0.15 kg
EAN	5702423084180
+ supply	Pin 1
- common	Pin 2
Accuracy, max. +/- FS [%]	1 %
Accuracy, typical +/- FS [%]	0.5 %
Adj. zero point and span	No
Ambient temperature range [°C] [Max]	85 °C
Ambient temperature range [°C] [Min]	-40 °C
Ambient temperature range [°F] [Max]	185 °F
Ambient temperature range [°F] [Min]	-40 °F
Approval	ATEX
Approval comments	ATEX Ex nA IIA T3 Gc

Compensated temp. range [°C] [Max]	80 °C
Compensated temp. range [°C] [Min]	0 °C
Compensated temp. range [°F] [Max]	176 °F
Compensated temp. range [°F] [Min]	32 °F
Electrical conn. Male/Female	Male and Female
Electrical connection	DIN-plug
Electrical connection size	Pg 9
Electrical connection standard	EN 175301-803-A
Enclosure rating IP	IP65
Flush diaphragm	No
High Clipping Level	22.4
Identical product	060G4079
International Article Number	5702423084180
Intrinsically safe	No
Low Clipping Level	3.6
Medium temperature range [°C] [Max]	85 °C
Medium temperature range [°C] [Min]	-40 °C
Medium temperature range [°F] [Max]	185 °F
Medium temperature range [°F] [Min]	-40 °F
Non-linearity BFSL ±FS [%]	0.5 %
Output signal	Current
Output signal [mA] [Max]	20 mA
Output signal [mA] [Min]	4 mA
Overload pressure max. [bar]	60 bar
Overload pressure max. [psi]	870 psi
Packing format	Multi pack

Pressure connection HEX [mm]	27 mm
Pressure connection size	1/4
Pressure connection standard	EN 837
Pressure connection type	G
Pressure Male/Female	Male
Pressure range [bar] [Max]	10 bar
Pressure range [bar] [Min]	0 bar
Pressure range [psi] [Max]	145.04 psi
Pressure range [psi] [Min]	0 psi
Pressure unit reference	Gauge (relative)
Product group	Sensors
Product name	Pressure transmitter
Pulse-snobber	No
Quantity per packing format	14 pc
Response time max. [ms]	4 ms
Specification key	MBS 3000-2011-A1AB04-0
Supply voltage [V] DC [Max]	30 V
Supply voltage [V] DC [Min]	10 V
Type	MBS 3000