



## Safety relief valve, SFA 15 148F3213

Pressure setting [bar]: 13, Connection type: G,  
Inlet connection size [in]: 3/4, Outlet connection  
size [in]: 1, Pressure certificate: Danfoss certificate  
included

Contact: 0982 67 24 67 -  
online@congnhieplanh.com

## Product details

|                              |                       |
|------------------------------|-----------------------|
| Gross weight                 | 1.97 kg               |
| Net weight                   | 1.93 kg               |
| EAN                          | 5702428194136         |
| Approval                     | CE<br>EAC<br>TS       |
| Category                     | IV                    |
| Certified Coef of Disc       | 0.73 kg               |
| Connection Internal/External | External              |
| Connection size [in]         | 1/2 in                |
| Connection size [mm]         | 15 mm                 |
| Connection standard          | ISO 228-1             |
| Connection type              | G                     |
| Direction                    | Angleway              |
| Flow area [in2]              | 0.206 in <sup>2</sup> |
|                              |                       |

|                                    |   |
|------------------------------------|---|
| <b>Flow area [mm<sup>2</sup>]</b>  | 133 mm <sup>2</sup>   |
| <b>Flow diameter [in]</b>          | 0.512 in  |
| <b>Flow diameter [mm]</b>          | 13 mm   |
| <b>Fluid Group</b>                 | I   |
| <b>Inlet connection size [in]</b>  | 3/4   |
| <b>Nominal diameter</b>            | DN < 15   |
| <b>Outlet connection size [in]</b> | 1   |
| <b>Packing format</b>              | Single pack   |
| <b>Pressure certificate</b>        | Danfoss certificate included  |
| <b>Pressure setting [bar]</b>      | 13 bar  |
| <b>Pressure setting [psig]</b>     | 189 psig  |
| <b>Product description</b>         | Safety Relief Valve   |
| <b>Product group</b>               | Safety relief valves  |
| <b>Product name</b>                | Safety relief valve   |
| <b>Quantity per packing format</b> | 1 pc  |
| <b>Refrigerants</b>                | R134a<br>R170<br>R22<br>R290<br>R401A<br>R402A<br>R404A<br>R407A<br>R407B<br>R407C<br>R407F<br>R409A<br>R410A<br>R421A<br>R502<br>R507<br>R600<br>R600a<br>R717<br>R744 |

|                                     |        |
|-------------------------------------|--------|
| <b>Temperature range [°C] [Max]</b> | 100 °C |
| <b>Temperature range [°C] [Min]</b> | -30 °C |
| <b>Temperature range [°F] [Max]</b> | 212 °F |
| <b>Temperature range [°F] [Min]</b> | -22 °F |
| <b>Type</b>                         | SFA 15 |