



## Solenoid valve, EVRA 15 032F6215

Function: NC, Inlet connection type: FLANGE,  
Outlet connection type: FLANGE, Manual operation  
option: Yes, Cv value [gal/min]: 3.120, Kv value  
[m<sup>3</sup>/h]: 2.700

**Contact: 0982 67 24 67 -  
online@congnhieplanh.com**

## Product details

<b>Gross weight</b>	1.76 kg
<b>Net weight</b>	1.52 kg
<b>EAN</b>	5702422178293
<b>Actuator system [mm]</b>	13.5 mm
<b>Ambient temperature</b>	-40 - 80 °C
<b>Ambient temperature range [°F] [Max]</b>	175 °F
<b>Ambient temperature range [°F] [Min]</b>	-40 °F
<b>Body material</b>	Cast iron
<b>Coil</b>	No
<b>Cv value [gal/min]</b>	3.12 gal/min
<b>Direction</b>	Straightway
<b>Flow direction indicator</b>	Embossed 1-way arrow
<b>Function</b>	NC

<b>Inlet connection type</b>	FLANGE
<b>Kv value [m³/h]</b>	2.7 m³/h
<b>Manual operation option</b>	Yes
<b>Max. Working Pressure [bar]</b>	42 bar
<b>Max. Working Pressure [psig]</b>	610 psig
<b>MaxOPD[bar] 10W AC</b>	21 bar
<b>MaxOPD[bar] 12W AC</b>	25 bar
<b>MaxOPD[bar] 20W DC</b>	18 bar
<b>MaxOPD[psi] 14W AC</b>	300 psi
<b>Medium temp. range note</b>	Defrost max 130°C/265°F
<b>Medium temperature range [°C] [Max]</b>	105 °C
<b>Medium temperature range [°C] [Min]</b>	-40 °C
<b>Medium temperature range [°F] [Max]</b>	221 °F
<b>Medium temperature range [°F] [Min]</b>	-40 °F
<b>MinODP [bar]</b>	0.05 bar
<b>MinODP [psi]</b>	0.72 psi
<b>Orifice size [mm]</b>	15 mm
<b>Outlet connection type</b>	FLANGE
<b>Packing format</b>	Single pack
<b>Parts Program name</b>	EVRA / EVRAT
<b>Product accessories</b>	Flanges Solenoid valve accessories
<b>Product group</b>	Solenoid valves
<b>Product name</b>	Solenoid valve

<b>Quantity per packing format</b>	1 pc
<b>Refrigerants</b>	R134a R22 R401A R402A R404A R407A R407B R407C R407F R409A R410A R421A R502 R507 R717
<b>Serviceable</b>	Solenoid valve spare parts
<b>Type</b>	EVRA 15
<b>Type designation</b>	Solenoid valve
<b>Valve operation</b>	SERVO-DIAPHRAGM